

MOTULE NISMO COMPETITION OIL 2108E 0W-30

Lubricant for naturally aspirated engines

100% Synthetic – Double Ester Technology

TYPE OF USE

Specially developed for NISSAN 3.5L, naturally aspirated engines VQ35DE, VQ35HR and VQ37HR fitted on NISSAN 350 Z, Skyline V35, Skyline V36, 350GT, Pathfinder, Altima, Maxima, Murano, Quest, but also on INFINITI EX35, FX35, M35, QX4, I35, G35, and requiring improved engine response and maximum power output.

Engine designed to run low viscosity lubricants and to minimize fuel dilution in the oil.

Other applications: Racing car, Drifting car, Tuning car. Check with engine tuner before use.

PERFORMANCES



NISMO (Nissan Motorsport International)

Double Ester Technology: maximum oil film resistance, balanced polarity, resistance increased at very high temperature.

This high performance lubricant is designed to deliver maximum power output on NISSAN and NISMO naturally aspirated engines running at high revs and under heavy loads.

Low viscosity grade 0W-30 reduces oil hydrodynamic friction, provides maximum power output mostly when oil is cold. Allows excellent oil flow into the engine, fastest oil pressure set up, faster rev raisings and better engine warming.

Performance approved successfully on many races such as the 24 Hours of Nurburgring, Tokachi with the NISMO Racing Team.

RECOMMENDATIONS

Oil change: 1865 Miles / 3000 Kms. Do not mix with others lubricants.

This product is not covered by any NISSAN Motor Company warranty.

PROPERTIES

SAE J 300	0W-30
ASTM D1298	0.851
ASTM D445	9.8 mm ² /s
ASTM D445	51.8 mm ² /s
ASTM D2270	176
ASTM D4741	3.22 mPa.s
ASTM D97	-36°C / -32.8°F
ASTM D92	226°C / 438.8°F
ASTM D2896	6.8 mg KOH/g
	ASTM D1298 ASTM D445 ASTM D445 ASTM D2270 ASTM D4741 ASTM D97 ASTM D92